


# DIN916

Stelschroef met binnenzeskant en kratereind  
 Gewindestifte mit Innensechskant und Ringschneide  
 Hexagon socket set screw with cup point



		d	M1,4	M1,6	(M 1,8)	M2	M2,5	M3	M4	M5	M6	M8	M10	M12	(M14)	M16	(M18)	M20	(M22)	M24		
d <sub>v</sub>	max.		0,7	0,8	0,9	1	1,2	1,4	2	2,5	3	5	6	8	9	10	12	14	16	16		
	min.		0,45	0,55	0,65	0,75	0,95	1,15	1,75	2,25	2,75	4,7	5,7	7,64	8,64	9,64	11,57	13,57	15,57	15,57		
e	min.		0,803	0,803	0,803	1,003	1,427	1,73	2,30	2,87	3,44	4,58	5,72	6,86	6,86	9,15	11,43	11,43	13,72	13,72		
	maat		0,7	0,7	0,7	0,9	1,3	1,5	2	2,5	3	4	5	6	6	8	10	10	12	12		
s	min.		0,711	0,711	0,711	0,889	1,27	1,52	2,02	2,52	3,02	4,02	5,02	6,02	6,02	8,025	10,025	10,025	12,032	12,032		
	max.		0,724	0,724	0,724	0,902	1,295	1,545	2,045	2,56	3,08	4,095	5,095	6,095	6,095	8,115	10,115	10,115	12,142	12,142		
t			0,6	0,7	0,8	0,8	1,2	1,2	1,5	2	2	3	4	4,8	5,6	6,4	7,2	8	9	10		
			1,4	1,5	1,6	1,7	2	2	2,5	3	3,5	5	6	8	9	10	11	12	13,5	15		
l																						
maat	min.	max.																				
2	1,80	2,20																				
2,5	2,30	2,70																				
3	2,80	3,20																				
(3,5)	3,26	3,74																				
4	3,76	4,24																				
5	4,76	5,24																				
6	5,76	6,24																				
8	7,71	8,29																				
10	9,71	10,29																				
12	11,65	12,35																				
(14)	13,65	14,35																				
16	15,65	16,35																				
(18)	17,65	18,35																				
20	19,58	20,42																				
(22)	21,58	22,42																				
25	24,58	25,42																				
(28)	27,58	28,42																				
30	29,58	30,42																				
35	34,5	35,5																				
40	39,5	40,5																				
45	44,5	45,5																				
50	49,5	50,5																				
55	54,4	55,6																				
60	59,4	60,6																				